



IPSO®

COMMERCIAL DRYER (REAR CONTROL) FOR OPL LAUNDRY APPLICATIONS

CD9E - CD9G



FEATURES

- **Superior airflow**
 - Advanced blower system produces airflow of 220 cu. Ft. per minute
 - Fast-drying results with advanced airflow pattern
 - Minimum dry time
- **Large capacity**
Large 7.0 ct ft. cylinder
- **Door opening of 2.06 sq. ft. for fast and easy loading and unloading**
- **Time savings**
Large, easy-clean lint filter is located upfront

CONTROL

- **E-Mech control**
The E-Mech Control on IPSO dryers assures reliable performance and helps optimize efficiency. The control panel offers convenient features - including an energy-saving cycle with an electronic timer.
- **Push-to-Start button**
Features simple, push-to-start activation with an 'In Use' LED light



visit laundrysolutions.com.au

OPL CD9 Rear Control Dryer specifications

	CD9E	CD9G
Control Option	E-mech Control	E-mech Control
Control Location	Rear	Rear
Drum		
Capacity (kg)	8.2	8.2
Volume (L)	198	198
Motor		
Power (KW)	0.25	0.25
Cabinet		
Cylinder Finish	Galvanized	Galvanized
Colours	White	White
Door Type	Solid	Solid
Heating		
Heat Source	Electric	Gas
Heating Power	4 kW	26.37 mJ
Connection		
Gas Inlet Connection (mm)	N/A	9.5
Exhaust Outlet Diameter (mm)	102	102
Exhaust Airflow (L/sec)	105	105
Operation		
Cycles	4	4
Cycle Indicator Lights	No	No
Power		
Electrical Requirements	20 AMP/240/50/1	10 AMP/240/50/1
Transport Data		
Gross Weight (KG)	73	73
Net Weight (KG)	68	68
Dimensions (mm)	1092h x 683w x 711d	1092h x 683w x 711d
Packing Dimensions (mm)	1156h x 762w x 864d	1156h x 762w x 864d

* heights may slightly vary depending on the levelling adjustments

