



COMMERCIAL DRYER (REAR CONTROL) FOR VENDED LAUNDRY APPLICATIONS

CD9EC - CD9GC



FEATURES

- **Superior airflow**
 - Advanced blower system produces airflow of 220 cu. Ft. per minute
 - Fast-drying results with advanced airflow pattern
 - Minimum dry time
- **Large capacity**
Large 7.0 ct ft. cylinder
- **Door opening of 2.06 sq. ft. for fast and easy loading and unloading**
- **Time savings**
Large, easy-clean lint filter is located upfront

CONTROL

- **Micro-Display Control (MDC)**
Offering the most essential features and programming options, the Micro-Display Control (MDC) on IPSO commercial dryers is user-friendly and features an attractive, easy-to-read design
- **Coin countdown start**
Displays vend price and countdown coin and cycle time
- **Touch pad control**
Offers touch pad selection and combines both temperature and cycle
- **Sound and light indicators**
Indicate cycle status and coin validation
- **Activation options**
Available with coin drop installed, card ready or coin ready models
- **Manual programming and audit**
Program and audit use via the control panel



visit laundrysolutions.com.au

Vended CD9C Rear Control Dryer specifications

	CD9EC	CD9GC
Control Option	Micro-Display Control	Micro-Display Control
Control Location	Rear	Rear
Drum		
Capacity (kg)	8.2	8.2
Volume (L)	198	198
Motor		
Power (KW)	0.25	0.25
Cabinet		
Cylinder Finish	Galvanized	Galvanized
Colours	White	White
Door Type	Solid	Solid
Heating		
Heat Source	Electric	Gas
Heating Power	4 kW	26.37 mJ
Connection		
Gas Inlet Connection (mm)	N/A	9.5
Exhaust Outlet Diameter (mm)	102	102
Exhaust Airflow (L/sec)	105	105
Operation		
Cycles	4	4
Cycle Indicator Lights	No	No
Power		
Electrical Requirements	20 AMP/240/50/1	10 AMP/240/50/1
Transport Data		
Gross Weight (KG)	73	73
Net Weight (KG)	68	68
Dimensions (mm)	1114h x 683w x 711d	1114h x 683w x 711d
Packing Dimensions (mm)	1156h x 762w x 864d	1156h x 762w x 864d

* heights may slightly vary depending on the levelling adjustments

